



POWER TO DO MORE



Go Further, For Longer

With enough power to recharge just about any smartphone 2-4 (GP28) or 4-6 (GS28) full times, you can remain connected for days, without being tethered. Plus, the carbon fiber texture provides a more secure grip, while the rounded shape is ergonomic, which makes it even more suitable for bringing along with you.



Secure hand grip with carbon fiber texture

Never Run On Empty Again

The GP28/GS28 has a built-in battery indicator with a digitized LED display. It doesn't get any more straightforward than a clear percentage of the remaining battery level. With this detailed indication, you'll always know when it's time to recharge the power bank, so you'll never have to worry about running on empty again.



Power Bank GP28/GS28

Features

- 10,000mAh (GP28) / 20,000mAh (GS28) capacity provides 2-4 (GP28) / 4-6 (GS28) full charge cycles on just about any smartphone
- 2 USB Type-A outputs charge up to 2 devices simultaneously
- Dual input (Micro-USB and Type-C) for more convenient charging options
- Carbon fiber texture provides a more secure grip, while the rounded shape is ergonomic
- Battery indicator shows exact remaining percentage on a digitized LED display
- smartSHIELD: Input High-Voltage Protection, Output High-Voltage Protection, Input Current Protection, Output Current Protection, Automatic Current Matching, Input Short-Circuit Protection, Output Short-Circuit Protection, Device Overcharge Protection, Reverse Charge Protection, Input Current Regulation, Static Resistance, and Fireproof Guard
- High quality Li-Polymer battery is safer, thinner, and provides a more effective charge
- Includes 1 USB Type-A to Type-C cable
- Safe to fly with
- Up to 2 million USD product liability insurance

Specifications

- Capacity: GP28: 10,000mAh / GS28: 20,000mAh
- Dimensions: GP28: 142.8mm x 67.6mm x 15.2mm
GS28: 149.2mm x 69.1mm x 27.6mm
- Weight: GP28: 228g ± 2g
GS28: 412g ± 2g
- Battery Type: Li-Polymer
- Material: Plastic + PC
- Color: Black, Pale Grey
- Input Power: Input Power: Micro-USB: 5V=2A ; Type-C: 5V=2A
- Output Power: USB1 (USB Type-A): 5V=2.1A, USB2 (USB Type-A): 5V=2.1A ; USB1+USB2: 5V=2.1A (max.)
- Available Interface (Input): Micro-USB, Type-C
- Available Interface (Output): USB Type-A (x2)
- Charging Time: GP28: 6 hours / GS28: 11 hours (2.0A power adapter suggested)
- Protection: smartSHIELD
- Operating Temperature: 10°C - 45°C
- Certification: CE, FCC, RoHS 2.0, PSE, Li-ion 00, BSMI, WEEE, Un38.3, 1.2M, MSDS
- Warranty: 13 months, 24 months (EU)



smartSENSE



smartFOCUS



smartSHIELD