

Industrial 3D TLC NAND 2.5" SATA SSD

SSD3K0 SERIES

SATA III

6.0 Gbit/s

SLC Cache

3D NAND



PRODUCT FEATURES

- High-Quality 3D NAND Flash Technology
- Global Wear Leveling and Early weak block retirement
- TRIM, NCQ, ATA Security Feature Set supported
- Lifetime Enhancements

Direct-to-TLC and SLC Cache enhancement to ensure the optimized WAF

Block/Page RAID function to ensure data recovery

- Reliable Industrial-grade circuit design and complete protection design with OVP, OCP, surge rejection, and Short protection.
- Power shielding firmware architecture to ensure power failure resilience
- AES256 Encryption and TCG Opal 2.0 compliant (by request)
- SP SMART Toolbox
- SP SMART Embedded and SMART IoT service (by request)
- Native Command Queuing up to 32 commands
- Garbage collection and TRIM Data Set Management command
- Global wear leveling algorithm evens program/erase count

PRODUCT SUMMARY

- Capacities : 64GB, 128GB, 256GB, 512GB, 1TB
- Form Factor : 2.5" SATA Solid State Drive (70 mm x 100 mm x 7 mm)
- Compliance : SATA Revision 3.1 - 6 Gbit/s (3 Gbit/s and 1.5 Gbit/s backward compatible)
- Command Sets : Supports ATA/ATAPI-8 and ACS-2
- Performance : *(estimated)*

	64GB	128GB	256GB	512GB	1TB
Sequential Read (MB/s Max.)	260	540	540	530	540
Sequential Write (MB/s Max.)	110	230	470	520	510
Random 4K Read (IOPS Max.)	9000	17000	28000	30000	29000
Random 4K Write (IOPS Max.)	28000	53000	82000	82000	85000

** Actual performance may vary based on the specific model and capacity*

- Operating Temperature Range :

Normal : 0°C to 70°C

- Storage Temperature Range : -55°C to 95°C
- Operating Voltage : 5 V \pm 10%
- Power Consumption : *(estimated)*

(Unit: mA)	64GB	128GB	256GB	512GB	1TB
Read (Max.)	TBD	330	340	TBD	TBD
Write (Max.)	TBD	280	380	TBD	TBD
Idle (Avg.)	TBD	< 85	< 85	TBD	TBD

** Actual value may vary based on the specific model and capacity*

- Data Retention @40 °C : 10 Years @ Life Begin; 1 Year @ Life End
- Endurance in Tera Bytes Written (TBW) : *(Unit: TB) (estimated)*

Workload	64GB	128GB	256GB	512GB	1TB
Sequential	91	182	364	728	1456
Enterprise	25	51	101	202	404

TBW is estimated by formula **TBW = (Capacity x PE Cycles) x (1+OP) x (WLE) / (WAF)**

OP (Over Provision) = (Physical Capacity / Logical Capacity)-1

WAF = Write Amplification Factor

WLE = Wear Leveling Efficiency could be different depended on the workload or usage containing data size and access rate.

Sequential workload: Sequential write workload which is generated by VDBENCH script and tested by VDBENCH

Enterprise workload: Follow JESD219A enterprise workload which is generated by VDBENCH script and tested by VDBENCH.

- Mechanical (IEC-60068) :

Vibration : 15G, 10 ~ 2001Hz

Drop : 76cm

Shock : 1,500G@0.6ms

- LDPC ECC engine and Block/Page RAID to ensure reliable 3K PE cycles
- Mean Time Between Failure : > 2,000,000 hours
- Data Reliability: Non-recover Read (UBER) $\leq 10^{-16}$
- Serious quality control and assurance

100% NAND Flash screening

High endurance product design with 3D NAND product offerings

Implement high/low temperature dynamic burn-in in each lot production to monitor production quality to meet design specification

Reliability criteria compliant with international standards IEC-60068/61000